

HPE Networking Instant On Access Point AP25 Flush Mount Sleeve

Installation Guide

Instant 



Hewlett Packard
Enterprise

Copyright Information

© Copyright 2024 Hewlett Packard Enterprise Development LP.

Hewlett Packard Enterprise Company
Attn: General Counsel
WW Corporate Headquarters
1701 E Mossy Oaks Rd, Spring, TX 77389
United States of America



The AP25 Flush Mount Sleeve lines up the exterior of the access point, offering a practical and aesthetic solution for concealment and customization.

Package Contents

Table 1: *Package Contents*

Item	Quantity
AP25 Flush Mount Sleeve	1

Installing the AP25 Flush Mount Sleeve onto the Access Point




It is recommended to install the wall/ceiling mount bracket prior to installing the flush mount sleeve.

To install the AP25 Flush Mount Sleeve to the access point, follow these steps:

1. Fit the bottom corner of the AP25 Flush Mount Sleeve around the access point, then press the sleeve onto the access point until it clicks into place.


Figure 1 *Attaching AP25 Flush Mount Sleeve onto access point*



Installing the Access Point (with Sleeve) to a Ceiling Rail

1. Hold the access point next to the ceiling rail with the mounting tabs of the mount bracket at approximately a 30-degree angle to the ceiling rail.
2. Pushing toward the ceiling rail, rotate the access point clockwise until the access point clicks into place on the ceiling rail.


Figure 2 *Installing the Access Point (with Sleeve) to a Ceiling Rail*



Removing the Access Point (with Sleeve) from a Ceiling Rail

1. Turn the access point (with sleeve) by hand counter-clockwise until the mounting tabs of the mount kit disengage from the ceiling rail.
2. After the access point (with sleeve) is removed from the ceiling rail, pull the sleeve off from the access point by hand.


Figure 3 *Removing the Access Point (with Sleeve) from a Ceiling Rail*



Installing the Access Point (with Sleeve) to a Wall

1. Install the mount bracket to the wall as per the installation instructions provided with the wall anchors.
2. Align the access point (with sleeve) with the mount bracket, placing the access point so that its mounting tabs are at an angle of approximately 30 degrees to the mount bracket.
3. Pushing towards the wall, rotate the access point (with sleeve) clockwise until it clicks into place.


Figure 4 *Installing the Access Point (with Sleeve) to a Wall*



Removing the Access Point (with Sleeve) from a Wall

1. Turn the access point (with sleeve) by hand counter-clockwise until the mounting tabs of the access point disengage from the mount bracket on the wall.
2. After the access point (with sleeve) is removed from the wall, pull the sleeve off from the access point by hand.

Figure 5 *Removing the Access Point (with Sleeve) from a Wall*



**Hewlett Packard
Enterprise**

© Copyright 2024 Hewlett Packard Enterprise Development LP.