

HPE Aruba Networking 630 Series Campus Access Points



What's new

- Three radios to extend the benefits of Wi-Fi 6E to the 6 GHz band –unlocking up to 1200 MHz of spectrum.
- Wider channels and less interference to deliver faster speeds for low-latency, bandwidth-hungry applications like high-definition video and augmented reality/virtual reality.
- Unique filtering capabilities to mitigate gaps in coverage and help minimize interference between the 5 GHz and 6 GHz bands.
- High availability with hitless failover for

Overview

HPE Aruba Networking 630 Series Campus Access Points (APs) are designed to take advantage of the 6 GHz band using three radios for comprehensive tri-band coverage. With 6 GHz, wireless capacity is more than doubled allowing enterprises to meet the today needs and plan for future growth. The Wi-Fi 6E APs allow countries to take advantage of Wi-Fi 6E once it is approved in country through automated notification and easy deployment of 6 GHz regulatory tables.

The 630 series delivers a maximum aggregate 3.9 Gbps data rate for higher throughput and faster speeds for fixed low power indoor use. With up to seven 160 MHz channels, the 630 APs maximize performance for low-latency, bandwidth-hungry applications. The ultra tri-band filtering eliminates interference between 5 GHz and 6 GHz and prevents gaps in channel coverage. To ensure high availability, the 630 series includes dual

Ethernet and power to help ensure business continuity.

- Automated notification and easy deployment of 6 GHz regulatory tables to allow countries to take advantage of Wi-Fi 6E once it is approved in country.

port hitless failover for ethernet and power.

Features

More Capacity and Wider Channels with Wi-Fi 6E

The HPE Aruba Networking 630 Series Campus Access Points deliver a maximum aggregate 3.9 Gbps data rate for higher throughput and faster speeds.

With up to seven 160 MHz channels, the APs help maximize performance for low-latency, bandwidth-hungry applications.

It is designed for low power indoor environments (LPI).

Less Interference and Fewer Coverage Gaps

The HPE Aruba Networking 630 Series Campus Access Points provide comprehensive tri-band coverage using three radios.

The HPE Aruba Networking unique ultra tri-band filtering mitigates interference among 5 GHz and 6 GHz radios and prevents gaps in channel coverage.

Since only Wi-Fi 6E enabled devices can operate in the 6 GHz band, it is less congested with no interference from legacy devices.

Extends capabilities of Wi-Fi 6 (802.11ax) APs

HPE Aruba Networking 630 Series Campus Access Points are based on the 802.11ax standard so multi-user efficiency and security features are applied to Wi-Fi 6E.

Unique HPE Aruba Networking capabilities include ClientMatch, Advanced Cellular Coexistence, and Intelligent Power Monitoring to optimize user experience and energy use.

Ensures Business Continuity and High Availability

High availability with two HPE Smart Rate Ethernet ports for 1-2.5 Gbps to offer true hitless failover for both data and power.

Cloud, controller, or controllerless operation modes address all campus, branch and remote use cases.



Technical specifications

HPE Aruba Networking 630 Series Campus Access Points

Certifications

UL2043 plenum rating
 Wi-Fi Alliance
 Wi-Fi CERTIFIED a, b, g, n, ac
 Wi-Fi CERTIFIED 6E (ax, 6GHz)
 WPA, WPA2 and WPA3 – Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)
 WMM, WMM-PS, Wi-Fi Vantage, W-Fi Agile Multiband
 Wi-Fi Location
 Passpoint (release 2)
 Bluetooth SIG
 Ethernet Alliance (POE, PD device, class 5)

Input voltage

12 Vdc (+/- 5%) or 48 Vdc (nominal) PoE

Regulatory

FCC/ISED; CE Marked; RED Directive 2014/53/EU; EMC Directive 2014/30/EU; Low Voltage Directive 2014/35/EU; UL/IEC/EN 60950; IEC/EN 62368-1; EN 60601-1-1, EN60601-1-2
 For more country-specific regulatory information and approvals, contact see your HPE Aruba Networking representative.

Regulatory considerations for AP-634:

The HPE Aruba Networking AP-634 will be offered in countries where there is an existing or clear and defined path to allow operation of 6 GHz radios with external connectorized antennas, either as a low power indoor or standard power product. Please contact your HPE Aruba Networking representative to confirm (existing or planned) availability for the country where the AP will be deployed.

Wi-Fi antenna

HPE Aruba Networking AP-634 (external antenna support): Two sets of two (female) RP-SMA connectors for external antennas (A0 & A1 corresponding with radio chains 0 and 1 for the 2.4 GHz and 5 GHz radios, and B0 and B1 corresponding with radio chains 0 and 1 for the 6 GHz radio). Worst-case internal loss between radio interface and external antenna connectors: 1.0 dB in 2.4 GHz, 1.0 dB in 5 GHz and 1.0 dB in 6 GHz.

HPE Aruba Networking AP-635 (internal antenna): Integrated downtilt omnidirectional antennas for 2x2 MIMO with peak antenna gain of 4.6 dBi in 2.4 GHz, 7.0 dBi in 5 GHz and 6.3 dBi in 6 GHz. Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The downtilt angle for maximum gain is roughly 30 to 40 degrees.

Combining the patterns of each of the antennas of the MIMO radios, the peak gain of the combined, average pattern is 2.9 dBi in 2.4 GHz, 4.9 dBi in 5 GHz and 4.3 dBi in 6 GHz.

Heat dissipation

66.3 BTU/hr worst case (PoE powered), 57.9 BTU/hr worst case (DC)

Connectivity, standard

WLAN: tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11ax 2x2 MIMO
 Bluetooth Low Energy (BLE5.0) and Zigbee (802.15.4) radio

Ports

E0, E1: Two Ethernet wired network ports (RJ-45), auto-sensing link speed (100/1000/2500BASE-T) and MDI/MDX
 DC power interface
 USB 2.0 host interface (Type A connector)
 Visual indicators (four multi-color LEDs)
 Reset button: factory reset, LED mode control

Mounting

The access points can be wall or ceiling mounted, using one of a range of optional mount kits. The AP-635 built-in antennas are optimized for horizontal orientation of the AP, mounted at a typical ceiling height.

Power consumption

23.8 W worst case (POE powered), 20.7 W worst case (DC). Excludes power needed to supply up to 5W to an attached USB device.

Radio coverage

Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11ax 2x2 MIMO

Warranty	Limited lifetime hardware warranty. See HPE Product Warranty for warranty and support information included with your product purchase.
Product dimensions	220mm x 220mm x 50mm
Weight	1300g

[1] Bluetooth is a trademark owned by its proprietor and used by Hewlett Packard Enterprise under license. All third-party marks are property of their respective owners

For additional technical information, available models and options, please reference the QuickSpecs

HPE Aruba Networking Services

HPE Aruba Networking services simplify and accelerate the network technology lifecycle, enabling your network to scale with better predictability and cost-effectiveness. Whether you operate your own network and need to improve your IT efficiencies, or you want to offload some of the burden, we have the services you need to reach your goals.

Learn more about what HPE Services - Aruba Networking has to offer at: arubanetworks.com/services/

Support Services

Our support portfolio provides the essential support elements as well as proactive and preventive features to help you improve your team's productivity and get the most from your network. Our support customers benefit from faster issue resolution, simplified operations and efficiencies, and reduced network issues.

Professional Services

With deep intellectual capital and purpose-built tools, our team delivers a range of standard and custom professional services designed to accelerate your value from HPE Aruba Networking technology.

- Project based services include:**
- Annual subscription services include:**
- Planning, audit, and assessment
 - Architecture review and design
 - Deployment, migration, and knowledge transfer
- Network optimization
 - Intelligent Operations
 - Customer Experience Management

Our [Education Services](#) allow your team to come up to speed quickly.

HPE GreenLake for Networking

Our NaaS solution, HPE Aruba Networking Managed Connectivity services, part of the HPE GreenLake services family, simplifies network operations, accelerates equipment handling, and increases the value of your HPE Aruba Networking network. If you need expert guidance and automation-based operations for your team, please explore the NaaS approach from HPE Aruba Networking [here](#).



Make the right purchase decision.
Contact our presales specialists.



Contact us

Visit [ArubaNetworks.com](https://www.arubanetworks.com)



**Hewlett Packard
Enterprise**

© Copyright 2024 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product
[PSN1013490535WWEN](#), October, 2024.